

Solid Carbide Slow Spiral Drill 2 Flute 135° Point 15° Helix AlTiN / Uncoated



Design Specs

- AlTiN Coated Other upon request
- Special Modifications/Lengths upon request

Application:

Outstanding performance in Aluminum, Brass alloys and Non-Ferrous Metals

2FL Slow Spiral Drill 135° Point

	•						
					Uncoated		Coated
Diame	eter L	OF	OAL	EDP#	Price	EDP#	Price
1/8	2 7	/8	2"	85000	\$12.12	85000C	\$13.94
- 170	, ,	, 0		05000	712.12	050000	715.71
3/1	6 1-	1/8	2-1/2	85020	\$17.57	85020C	\$20.50
1//	1 1	2 /0	2 1/2	05040	¢25.12	050406	¢20.26
1/4	1-	3/8	2-1/2	85040	\$25.13	85040C	\$29.36
5/1	6 1-	5/8	3"	85060	\$36.67	85060C	\$41.72
					•		-
3/8	3 1-	3/4	3″	85080	\$48.82	85080C	\$54.18
7/1	6 2-	1/8	3-1/2	85100	\$72.31	85100C	\$81.47
771	0 2	170	J 1/2	05100	7/2.51	051000	701.47
1/2	2 2-	1/4	4"	85120	\$87.24	85120C	\$97.13
					= .		

^{*}Non-standard requirements are available upon request including length, chamfer and radius with different tolerances

Cutting Diameter +.000/-.002

Shank Diameter -.0001/-.0004

Length of Cut +.025/+0.50

Overall Length ± .050