

Solid Carbide Stright Flute Drill 2 Flute 135° Point AlTiN / Uncoated



Design Specs

- AlTiN Coated Other upon request
- Special Modifications/Lengths upon request

Application:

Outstanding performance in Aluminum, Brass alloys and Non-Ferrous Metals

2FL Stright Flute Drill 135° Point

Diameter	LOE	OAL	EDD#	Uncoated	EDD#	Coated
Diameter	LOF	OAL	EDP#	Price	EDP#	Price
3/16	3/4	2-1/2	86000	\$14.04	86000C	\$17.07
1/4	1"	2-1/2	86020	\$20.50	86020C	\$24.62
5/16	1-1/4	2-1/2	86040	\$30.18	86040C	\$35.23
3/8	1-1/4	3″	86060	\$40.79	86060C	\$46.25
7/16	1-1/4	3″	86080	\$55.72	86080C	\$62.83
1/2	1-1/4	3″	86100	\$61.80	86100C	\$69.01
9/16	1-1/2	3-1/2	86120	\$81.58	86120C	\$91.98
5/8	1-1/2	3-1/2	86140	\$90.74	86140C	\$101.97
3/4	1-1/2	4"	86160	\$103.21	86160C	\$117.11

^{*}Non-standard requirements are available upon request including length, chamfer and radius with different tolerances

Cutting Diameter +.000/-.002

Shank Diameter -.0001/-.0004

Length of Cut +.025/+0.50

Overall Length ± .050

